



◆ SPECIFICATION

Model NO.	HDAN-30MZF2								
Video Output Mode	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS	CVI / AHD / TVI / CVBS
Camera									
Image Sensor	OV9732	IMX225	S3130	F22	IMX323	IMX323	IMX290	IMX323	IMX290
DSP	HTC960E	HTC960E	HTC960E	HTC1080E	FH8550D	HTC1088	HTC1088	HTC1088	HTC1088
Image Resolution	720P	960P / 960H	960P / 960H	1080P	1080P	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H
Effective Pixels	1280*720	1280*960	1280*960	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080
TV System	PAL/NTSC								
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s								
S/N Ratio	≥50dB								
Scanning System	Progressive Scan								
Lens									
Focus Length	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	2.8-8mm	2.8-8mm
Focus Control	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Auto	Auto
Lens Type	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Motor Zoom Auto Focus	Motor Zoom Auto Focus
Pixels	2M Pixels	2M Pixels	2M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels
Auto Iris Support	NO	NO	NO	NO	NO	NO	NO	NO	NO
Night Vision									
Infrared LED	42μ x 2PCS								
Infrared Distance	25 M								
IR Status	Under 10 Lux by CDS								
IR Power On	CDS Auto Control								
Camera Features									
Day/Night	YES	YES	YES	YES	YES	YES	YES	YES	YES
OSD Menu Language	YES	YES	YES	YES	YES	YES	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO
Noise Reduction	DNR	DNR	DNR	DNR	3DNR	3DNR	3DNR	3DNR	3DNR
Picture Adjustment	YES	YES	YES	YES	YES	YES	YES	YES	YES
WDR	YES	YES	YES	YES	YES	YES	YES	YES	YES
OSD Support	YES	YES	YES	YES	YES	YES	YES	YES	YES
UTC	YES	YES	YES	YES	YES	YES	YES	YES	YES
General									
Housing	Metal, IP66								
Bracket	YES								
Dual Voltage	NO								
IR Cut Filter	YES								
Heater	NO								
Operation Temperature	-10℃ ~ +50℃ RH95% Max								
Storage Temperature	-20℃ ~ +60℃ RH95% Max								
Power Source	DC12V±10%, 700mA								
Dimension	157(W) x 70(H) x 66(D)mm								
Weight	650g								